

**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOE OT AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE OT AND MUST BE RETURNED TO BOE OT UPON ITS REQUEST

# HT140WXB-601

## Product Specification

### Rev. A

**BEIJING BOE OPTOELECTRONICS TECHNOLOGY**

SPEC. NUMBER

-

PRODUCT GROUP

TFT-LCD

REV.

P1

ISSUE DATE

2010.12.10

PAGE

1 OF 35

## REVISION HISTORY

[illegible]

|              |                                    |         |
|--------------|------------------------------------|---------|
| SPEC. NUMBER | SPEC TITLE                         | PAGE    |
| –            | HT140WXB-601 Product Specification | 2 OF 35 |

京东方  
BOE**PRODUCT GROUP**

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

## Contents

| No.  | Items                                                | Page |
|------|------------------------------------------------------|------|
| 1.0  | General Description                                  | 4    |
| 2.0  | Absolute Maximum ratings                             | 6    |
| 3.0  | Electrical specifications.                           | 7    |
| 4.0  | Optical specifications.                              | 9    |
| 5.0  | Interface Connection                                 | 14   |
| 6.0  | Signal Timing Specification                          | 18   |
| 7.0  | Signal Timing waveforms                              | 20   |
| 8.0  | Input Signals, Display Colors & Gray Scale of Colors | 22   |
| 9.0  | Power Sequence                                       | 23   |
| 10.0 | Connector description                                | 24   |
| 11.0 | Mechanical Characteristics                           | 25   |
| 12.0 | Reliability Test                                     | 26   |
| 13.0 | Handling & Cautions.                                 | 26   |
| 14.0 | Label                                                | 27   |
| 15.0 | Packing information                                  | 29   |
| 16.0 | Mechanical Outline Dimension                         | 30   |
| 17.0 | EDID Table                                           | 32   |

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

3 OF 35

**京东方**  
**BOE****PRODUCT GROUP**

TFT LCD PRODUCT

REV


P1

ISSUE DATE

2010.12.10

**1.0 GENERAL DESCRIPTION****1.1 Introduction**

HT140WXB-601 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 14.0 inch diagonally measured active area with WXGA resolutions (1366 horizontal by 768 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical Stripe and this module can display 262,144 colors. The TFT-LCD panel used for this module is a low reflection and higher color type. Therefore, this module is suitable for Notebook PC. The LED Driver for back-light driving is built in this model. All input signals are LVDS interface compatible.

**1.2 Features**

- 1 Channel LVDS Interface with 1 pixel / clock
- Thin and light weight
- 6-bit color depth, display 262K colors
- Single LED Lighting Bar. (Top side/Horizontal Direction)
- Data enable signal mode
- Side Mounting Frame
- Green Product (RoHS & Halogen free product)
- On board LED Driving circuit
- Low driving voltage and low power consumption
- On board EDID chip

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

4 OF 35

|                                                                                                         |                      |     |            |
|---------------------------------------------------------------------------------------------------------|----------------------|-----|------------|
|  <div>京东方<br/>BOE</div> | <b>PRODUCT GROUP</b> | REV | ISSUE DATE |
|                                                                                                         | TFT LCD PRODUCT      | P1  | 2010.12.10 |

1.3 Application

- Notebook PC (Wide type)

1.4 General Specification

The followings are general specifications at the model HT140WXB-601. (listed in Table 1.)

<Table 1. General Specifications>

| Parameter           | Specification                            | Unit   | Remarks |
|---------------------|------------------------------------------|--------|---------|
| Active area         | 309.4(H) × 173.95(V)                     | mm     |         |
| Number of pixels    | 1366 (H) × 768 (V)                       | pixels |         |
| Pixel pitch         | 0.2265(H) × 0.2265 (V)                   | mm     |         |
| Pixel arrangement   | RGB Vertical stripe                      |        |         |
| Display colors      | 262K                                     | colors |         |
| Display mode        | Normally White                           |        |         |
| Dimensional outline | 323.5 (H) × 192 (V) × 5.2 (D:max)        | mm     |         |
| Weight              | 350 (max)                                | g      |         |
| Surface treatment   | Anti-Glare (Haze 40)                     |        |         |
| Back-light          | Upper edge side, 1-LED Lighting Bar type |        | Note 1  |
| Power consumption   | P <sub>D</sub> : 1.1 (max)               | W      |         |
|                     | P <sub>BL</sub> : 3.0 (max)              | W      |         |
|                     | P <sub>total</sub> : 4.1 (max)           | W      |         |

Notes : 1. LED Lighting Bar (40\*LED Array)

|              |                                    |         |
|--------------|------------------------------------|---------|
| SPEC. NUMBER | SPEC TITLE                         | PAGE    |
| -            | HT140WXB-601 Product Specification | 5 OF 35 |



## PRODUCT GROUP

REV

ISSUE DATE

TFT LCD PRODUCT

P1

2010.12.10

## 2.0 ABSOLUTE MAXIMUM RATINGS


The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings>

Ta=25+/-2°C

| Parameter             | Symbol   | Min.         | Max.         | Unit | Remarks |
|-----------------------|----------|--------------|--------------|------|---------|
| Power Supply Voltage  | $V_{DD}$ | -0.3         | 4.0          | V    | Note 1  |
| Logic Supply Voltage  | $V_{IN}$ | $V_{SS}-0.3$ | $V_{DD}+0.3$ | V    |         |
| Operating Temperature | $T_{OP}$ | 0            | +50          | °C   | Note 2  |
| Storage Temperature   | $T_{ST}$ | -20          | +60          | °C   |         |

- Notes : 1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.
2. Temperature and relative humidity range are shown in the figure below.  
 95 % RH Max. ( 40 °C ≥ Ta)  
 Maximum wet - bulb temperature at 39 °C or less. (Ta > 40 °C) No condensation.



SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

6 OF 35



# PRODUCT GROUP

REV

ISSUE DATE

TFT LCD PRODUCT

P1

2010.12.10

## 3.0 ELECTRICAL SPECIFICATIONS

### 3.1 Electrical Specifications

&lt; Table 3. Electrical specifications &gt;


Ta=25+/-2°C

| Parameter                              |                    | Min. | Typ. | Max. | Unit | Remarks                     |
|----------------------------------------|--------------------|------|------|------|------|-----------------------------|
| Power Supply Voltage                   | V <sub>DD</sub>    | 3.0  | 3.3  | 3.6  | V    | Note 1                      |
| Permissible Input Ripple Voltage       | V <sub>RF</sub>    | -    | -    | 100  | mV   | At V <sub>DD</sub> = 3.3V   |
| Power Supply Current                   | I <sub>DD</sub>    | -    | 205  | -    | mA   | Note 1                      |
| Positive-going Input Threshold Voltage | V <sub>IT+</sub>   | -    | -    | 100  | mV   | V <sub>cm</sub> = 1.2V typ. |
| Negative-going Input Threshold Voltage | V <sub>IT-</sub>   | -100 | -    | -    | mV   |                             |
| Differential Input Voltage             | V <sub>ID</sub>    | 200  | -    | 600  | mV   |                             |
| Power Consumption                      | P <sub>D</sub>     | -    | 0.68 | 1.1  | W    | Note 1                      |
|                                        | P <sub>BL</sub>    | -    | 2.85 | 3.0  | W    | Note 2                      |
|                                        | P <sub>total</sub> | -    | 3.53 | 4.1  | W    |                             |

Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.  
The current draw and power consumption specified is for 3.3V at 25°C.

a) Typ : Window XP pattern

b) Max : Vertical 2 line skip pattern



2. Calculated value for reference (V<sub>LED</sub> × I<sub>LED</sub>)

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

7 OF 35



# PRODUCT GROUP

REV

ISSUE DATE

TFT LCD PRODUCT

P1

2010.12.10

## 3.0 ELECTRICAL SPECIFICATIONS

### 3.2 Backlight Unit

< Table 4. LED Driving guideline specifications >

Ta=25+/-2°C

| Parameter                           |                  | Min.   | Typ. | Max.   | Unit | Remarks               |
|-------------------------------------|------------------|--------|------|--------|------|-----------------------|
| LED Forward Voltage                 | V <sub>F</sub>   | 3.0    | 3.2  | 3.4    | V    | -                     |
| LED Forward Current                 | I <sub>F</sub>   | -      | 20   |        | mA   | -                     |
| LED Power Consumption               | P <sub>LED</sub> |        | 2.85 | 3.0    | W    | Note 1                |
| LED Life-Time                       | N/A              | 15,000 | -    | -      | Hour | I <sub>F</sub> = 20mA |
| Power supply voltage for LED Driver | V <sub>LED</sub> | 6      | 12   | 21     | V    |                       |
| EN Control Level                    | Backlight on     | 2.0    |      | 5.0    | V    |                       |
|                                     | Backlight off    | 0      |      | 1.0    | V    |                       |
| PWM Control Level                   | PWM High Level   | 2.0    |      | 5.0    | V    |                       |
|                                     | PWM Low Level    | 0      |      | 0.1    | V    |                       |
| PWM Control Frequency               | F <sub>PWM</sub> | 180    | -    | 10,000 | Hz   |                       |
| Duty Ratio                          | -                | 5      | -    | 100    | %    |                       |

Notes : 1. Power supply voltage 12V for LED Driver, Driver efficiency 90%,

Calculator Value for reference  $I_F \times V_F \times 40 / 0.9 = P_{LED}$

2. The LED Life-time define as the estimated time to 50% degradation of initial luminous.

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

8 OF 35





京东方  
BOE

## PRODUCT GROUP

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

## 4.0 OPTICAL SPECIFICATION

### 4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance  $\leq 1$  lux and temperature =  $25 \pm 2^\circ\text{C}$ ) with the equipment of Luminance meter system (Goniometer system and TOPCON BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of  $\theta$  and  $\Phi$  equal to  $0^\circ$ . We refer to  $\theta\Phi=0$  ( $=\theta_3$ ) as the 3 o'clock direction (the "right"),  $\theta\Phi=90$  ( $=\theta_{12}$ ) as the 12 o'clock direction ("upward"),  $\theta\Phi=180$  ( $=\theta_9$ ) as the 9 o'clock direction ("left") and  $\theta\Phi=270$  ( $=\theta_6$ ) as the 6 o'clock direction ("bottom"). While scanning  $\theta$  and/or  $\Phi$ , the center of the measuring spot on the Display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be  $3.3 \pm 0.3\text{V}$  at  $25^\circ\text{C}$ . Optimum viewing angle direction is 6 'clock.

### 4.2 Optical Specifications

<Table 5. Optical Specifications>

| Parameter                        |            | Symbol          | Condition                         | Min.  | Typ.  | Max.  | Unit              | Remark |
|----------------------------------|------------|-----------------|-----------------------------------|-------|-------|-------|-------------------|--------|
| Viewing Angle range              | Horizontal | $\Theta_3$      | CR > 10                           | 40    | 45    | -     | Deg.              | Note 1 |
|                                  |            | $\Theta_9$      |                                   | 40    | 45    | -     | Deg.              |        |
|                                  | Vertical   | $\Theta_{12}$   |                                   | 15    | 20    | -     | Deg.              |        |
|                                  |            | $\Theta_6$      |                                   | 30    | 40    | -     | Deg.              |        |
| Luminance Contrast ratio         |            | CR              | $\Theta = 0^\circ$                | 300   | 400   |       |                   | Note 2 |
| Luminance of White               | 5 Points   | $Y_w$           | $\Theta = 0^\circ$<br>ILED = 20mA | 170   | 200   | -     | cd/m <sup>2</sup> | Note 3 |
| White Luminance uniformity       | 5 Points   | $\Delta Y_5$    |                                   | 80    | -     | -     |                   | Note 4 |
|                                  | 13 Points  | $\Delta Y_{13}$ |                                   | 65    | -     | -     |                   |        |
| White Chromaticity               |            | $x_w$           | $\Theta = 0^\circ$                | 0.283 | 0.313 | 0.343 |                   | Note 5 |
|                                  |            | $y_w$           |                                   | 0.299 | 0.329 | 0.359 |                   |        |
| Reproduction of color            | Red        | $x_R$           | $\Theta = 0^\circ$                | 0.552 | 0.582 | 0.612 |                   |        |
|                                  |            | $y_R$           |                                   | 0.323 | 0.353 | 0.383 |                   |        |
|                                  | Green      | $x_G$           |                                   | 0.295 | 0.325 | 0.355 |                   |        |
|                                  |            | $y_G$           |                                   | 0.519 | 0.549 | 0.579 |                   |        |
|                                  | Blue       | $x_B$           |                                   | 0.120 | 0.150 | 0.180 |                   |        |
|                                  |            | $y_B$           |                                   | 0.080 | 0.110 | 0.140 |                   |        |
| Response Time (Rising + Falling) |            | T <sub>RT</sub> | Ta= 25° C<br>$\Theta = 0^\circ$   | -     | 8     | 16    | ms                | Note 6 |
| Cross Talk                       |            | CT              | $\Theta = 0^\circ$                | -     | -     | 2.0   | %                 | Note 7 |

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

9 OF 35

京东方  
BOE**PRODUCT GROUP**

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

Notes : 1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).

2. Contrast measurements shall be made at viewing angle of  $\Theta = 0$  and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state .  
(see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.
4. The White luminance uniformity on LCD surface is then expressed as :  $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points}$  (see FIGURE 2 and FIGURE 3).
5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
6. The electro-optical response time measurements shall be made as FIGURE 4 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is  $T_r$ , and 90% to 10% is  $T_d$ .
7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark. (See FIGURE 5).

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

10 OF 35



## PRODUCT GROUP

REV

ISSUE DATE


TFT LCD PRODUCT

P1

2010.12.10


### 4.3 Optical measurements

Figure 1. Measurement Set Up



Optical characteristics measurement setup

Figure 2. White Luminance and Uniformity Measurement Locations (5 points)



Note:

- Center point is defined as point 55
- 5 points are defined as point 33,37,55,73,77
- 11 points are defined as point 11,22,33,44,55, 66,77,88,99,19,91

SPEC. NUMBER

-

SPEC TITLE


HT140WXB-601 Product Specification

PAGE

11 OF 35


|                                                                                                         |                 |     |            |
|---------------------------------------------------------------------------------------------------------|-----------------|-----|------------|
|  <div>京东方<br/>BOE</div> | PRODUCT GROUP   | REV | ISSUE DATE |
|                                                                                                         | TFT LCD PRODUCT | P1  | 2010.12.10 |

Figure 3. Uniformity Measurement Locations (13 points)



The White luminance uniformity on LCD surface is then expressed as :  $\Delta Y5$  = Minimum Luminance of five points / Maximum Luminance of five points (see FIGURE 2) ,  $\Delta Y13$  = Minimum Luminance of 13 points /Maximum Luminance of 13 points (see FIGURE 3).

Figure 4. Response Time Testing



The electro-optical response time measurements shall be made as shown in FIGURE 4 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Td and 90% to 10% is Tr.

|              |                                    |          |
|--------------|------------------------------------|----------|
| SPEC. NUMBER | SPEC TITLE                         | PAGE     |
| —            | HT140WXB-601 Product Specification | 12 OF 35 |



# PRODUCT GROUP

REV


ISSUE DATE

TFT LCD PRODUCT

P1

2010.12.10

## Figure 5. Cross Modulation Test Description



$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_B} \right| \times 100$$

Where:

$Y_A$  = Initial luminance of measured area ( $\text{cd/m}^2$ )

$Y_B$  = Subsequent luminance of measured area ( $\text{cd/m}^2$ )

The location measured will be exactly the same in both patterns

Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance ( $Y_A$ ) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance ( $Y_B$ ) of that same area when any adjacent area is driven dark (Refer to FIGURE 5).

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

13 OF 35



京东方  
BOE

## PRODUCT GROUP

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

## 5.0 INTERFACE CONNECTION.

### 5.1 Electrical Interface Connection

The electronics interface connector is I-PEX 20455-040E-12 or Compatible or equivalent. The mating connector part number is I-PEX 20455-040T-11 or Compatible. The connector interface pin assignments are listed in Table 6.

<Table 6. Pin Assignments for the Interface Connector>

| Terminal | Symbol    | Functions                         |
|----------|-----------|-----------------------------------|
| Pin No.  | Symbol    | Description                       |
| 1        | NC        | No Connection                     |
| 2        | VDDIN     | Power Supply, 3.3V (typ.)         |
| 3        | VDDIN     | Power Supply, 3.3V (typ.)         |
| 4        | VDC       | VDC 3.3V power for EDID           |
| 5        | BISTC     | BIST control(Note.1)              |
| 6        | CLK EDID  | EDID Clock                        |
| 7        | Data EDID | EDID Data                         |
| 8        | RxIN0-    | Transmission Data of 0 Negative - |
| 9        | RxIN0+    | Transmission Data of 0 Positive + |
| 10       | GND       | Ground                            |
| 11       | RxIN1-    | Transmission Data of 1 Negative - |
| 12       | RxIN1+    | Transmission Data of 1 Positive + |
| 13       | GND       | Ground                            |
| 14       | RxIN2-    | Transmission Data of 2 Negative - |
| 15       | RxIN2+    | Transmission Data of 2 Positive + |
| 16       | GND       | Ground                            |
| 17       | RxCLKIN-  | Sampling Clock of Negative -      |
| 18       | RxCLKIN+  | Sampling Clock of Positive +      |
| 19       | CE_EN     | Color Engine Enable               |
| 20       | NC        | No Connection                     |
| 21       | NC        | No Connection                     |
| 22       | GND       | Ground                            |
| 23       | NC        | No Connection                     |
| 24       | NC        | No Connection                     |
| 25       | GND       | Ground                            |
| 26       | (CE)      | LCD internal use only             |
| 27       | (CTL)     |                                   |
| 28       | GND       | Ground                            |
| 29       | NC        | No Connection                     |
| 30       | NC        | No Connection                     |

SPEC. NUMBER

—

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

14 OF 35

**PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

P1

2010.12.10

| Terminal | Symbol   | Functions                   |
|----------|----------|-----------------------------|
| Pin No.  | Symbol   | Description                 |
| 31       | VLED_GND | LED Ground                  |
| 32       | VLED_GND | LED Ground                  |
| 33       | VLED_GND | LED Ground                  |
| 34       | NC       | No Connection               |
| 35       | PWM      | System PWM Signal Input     |
| 36       | LED_EN   | LED enable pin(+3.3V Input) |
| 37       | DCR_EN   | Dynamic Backlight Enable    |
| 38       | VLED     | LED Power Supply 6V-21V     |
| 39       | VLED     | LED Power Supply 6V-21V     |
| 40       | VLED     | LED Power Supply 6V-21V     |

## Note.1

-BIST="H (3.3V)" : Display BIST pattern @ No LVDS CLK or DE

(white->black->red->green->blue->white...)

-BIST="L(GND or NC)" : Display black pattern @ No LVDS CLK or DE

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

15 OF 35





京东方  
BOE

## PRODUCT GROUP

TFT LCD PRODUCT


REV

P1

ISSUE DATE


2010.12.10

### 5-2. LVDS Interface



Note. Transmitter : Thine THC63LVDM63A or equivalent.  
Transmitter is not contained in Module.

### 5.3.LVDS Input signal



Note. Pin connection in case of using Thine THC63LVDM63A

SPEC. NUMBER

—

SPEC TITLE

HT140WXB-601 Product Specification

PAGE


16 OF 35



|                                                                                             |                 |     |            |
|---------------------------------------------------------------------------------------------|-----------------|-----|------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE |
|                                                                                             | TFT LCD PRODUCT | P1  | 2010.12.10 |

5.3 Data Input Format

<Table 6. Pin Assignments for the Interface Connector>



5.4 Back-light & LCM Interface Connection

Interface Connector: MS24022P10 or Equivalent

<Table 7. Pin Assignments for the BLU & LCM Connector>

| Pin No. | Symbol | Description          | Pin No. | Symbol | Description            |
|---------|--------|----------------------|---------|--------|------------------------|
| 1       | Vout   | LED anode connection | 6       | LED1   | LED cathode connection |
| 2       | Vout   | LED anode connection | 7       | LED2   | LED cathode connection |
| 3       | Vout   | LED anode connection | 8       | LED3   | LED cathode connection |
| 4       | NC     | No Connection        | 9       | LED4   | LED cathode connection |
| 5       | NC     | No Connection        | 10      | LED5   | LED cathode connection |

|              |                                    |          |
|--------------|------------------------------------|----------|
| SPEC. NUMBER | SPEC TITLE                         | PAGE     |
| —            | HT140WXB-601 Product Specification | 17 OF 35 |



## PRODUCT GROUP

REV

ISSUE DATE

TFT LCD PRODUCT

P1

2010.12.10

### 6.0 SIGNAL TIMING SPECIFICATION

6.1 The HT140WXB-501 is operated by the DE only.

| Item                      |           | Symbols | Min  | Typ  | Max  | Unit   |
|---------------------------|-----------|---------|------|------|------|--------|
| Clock                     | Frequency | 1/Tc    | 45   | 72.3 | 76.3 | MHz    |
|                           | High Time | Tch     | -    | 4/7  | -    | Tc     |
|                           | Low Time  | Tcl     | -    | 3/7  | -    | Tc     |
| Frame Period              |           | Tv      | 778  | 790  | 802  | lines  |
|                           |           |         | 40   | 60   | -    | Hz     |
|                           |           |         | -    | 16.7 | -    | ms     |
| Vertical Display Period   |           | Tvd     | 768  | 768  | 768  | lines  |
| One line Scanning Period  |           | Th      | 1446 | 1526 | 1586 | clocks |
| Horizontal Display Period |           | Thd     | 1366 | 1366 | 1366 | clocks |

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

18 OF 35



# PRODUCT GROUP

REV

ISSUE DATE

TFT LCD PRODUCT

P1


2010.12.10

## 6.2 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 8.

<Table 8. LVDS Rx Interface Timing Specification>

| Item           | Symbol | Min            | Typ        | Max            | Unit | Remark |
|----------------|--------|----------------|------------|----------------|------|--------|
| CLKIN Period   | tRCIP  | -              | 13.83      | 25             | nsec |        |
| CLK Difference | tCdiff | -tRCIP*(3/7)   | 0          | +tRCIP*(3/7)   | nsec |        |
| Input Data 0   | tRIP1  | -0.4           | 0.0        | +0.4           | nsec |        |
| Input Data 1   | tRIP0  | tRIP/7-0.4     | tRIP/7     | tRIP/7+0.4     | nsec |        |
| Input Data 2   | tRIP6  | 2 × tRIP/7-0.4 | 2 × tRIP/7 | 2 × tRIP/7+0.4 | nsec |        |
| Input Data 3   | tRIP5  | 3 × tRIP/7-0.4 | 3 × tRIP/7 | 3 × tRIP/7+0.4 | nsec |        |
| Input Data 4   | tRIP4  | 4 × tRIP/7-0.4 | 4 × tRIP/7 | 4 × tRIP/7+0.4 | nsec |        |
| Input Data 5   | tRIP3  | 5 × tRIP/7-0.4 | 5 × tRIP/7 | 5 × tRIP/7+0.4 | nsec |        |
| Input Data 6   | tRIP2  | 6 × tRIP/7-0.4 | 6 × tRIP/7 | 6 × tRIP/7+0.4 | nsec |        |



$$* V_{diff} = (RXO/Ez+) - (RXO/Ez-), \dots, (RXO/ECLK+) - (RXO/ECLK-)$$

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

19 OF 35



京东方  
BOE

## PRODUCT GROUP

TFT LCD PRODUCT

REV


P1

ISSUE DATE

2010.12.10


## 7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL

### 7.1 Sync Timing Waveforms



- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

### 7.2 Vertical Timing Waveforms



SPEC. NUMBER

—

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

20 OF 35



# PRODUCT GROUP

REV



ISSUE DATE

TFT LCD PRODUCT

P1

2010.12.10

## 7.3 Horizontal Timing Waveforms



SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

21 OF 35



京东方  
BOE

## PRODUCT GROUP

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

## 8.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

|                             | Colors &<br>Gray scale | Data signal |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |
|-----------------------------|------------------------|-------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
|                             |                        | R0          | R1 | R2 | R3 | R4 | R5 | G0 | G1 | G2 | G3 | G4 | G5 | B0 | B1 | B2 | B3 | B4 | B5 |
| Basic colors                | Black                  | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | Blue                   | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  |
|                             | Green                  | 0           | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | Light Blue             | 0           | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
|                             | Red                    | 1           | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | Purple                 | 1           | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  |
|                             | Yellow                 | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | White                  | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
| Gray scale of Red           | Black                  | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | △                      | 1           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | Darker                 | 0           | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | △                      | ↑           |    |    |    |    | ↑  |    |    |    |    | ↑  |    |    |    |    |    |    |    |
|                             | ▽                      | ↓           |    |    |    |    | ↓  |    |    |    |    | ↓  |    |    |    |    |    |    |    |
|                             | Brighter               | 1           | 0  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | ▽                      | 0           | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | Red                    | 1           | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
| Gray scale of Green         | Black                  | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | △                      | 0           | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | Darker                 | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | △                      | ↑           |    |    |    |    | ↑  |    |    |    |    | ↑  |    |    |    |    |    |    |    |
|                             | ▽                      | ↓           |    |    |    |    | ↓  |    |    |    |    | ↓  |    |    |    |    |    |    |    |
|                             | Brighter               | 0           | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | ▽                      | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | Green                  | 0           | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  |
| Gray scale of Blue          | Black                  | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | △                      | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  |
|                             | Darker                 | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  |
|                             | △                      | ↑           |    |    |    |    | ↓  |    |    |    |    | ↑  |    |    |    |    |    |    |    |
|                             | ▽                      | ↓           |    |    |    |    | ↓  |    |    |    |    | ↓  |    |    |    |    |    |    |    |
|                             | Brighter               | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 1  | 1  | 1  | 1  |
|                             | ▽                      | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  |
|                             | Blue                   | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1  | 1  | 1  | 1  | 1  |
| Gray scale of White & Black | Black                  | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                             | △                      | 1           | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  |
|                             | Darker                 | 0           | 1  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0  | 0  | 0  |
|                             | △                      | ↑           |    |    |    |    | ↑  |    |    |    |    | ↑  |    |    |    |    |    |    |    |
|                             | ▽                      | ↓           |    |    |    |    | ↓  |    |    |    |    | ↓  |    |    |    |    |    |    |    |
|                             | Brighter               | 1           | 0  | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 1  | 1  | 1  |
|                             | ▽                      | 0           | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 1  | 1  | 1  | 1  |
|                             | White                  | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  |

SPEC. NUMBER

—

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

22 OF 35



## PRODUCT GROUP

REV

ISSUE DATE


TFT LCD PRODUCT

P1

2010.12.10

### 9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- $T1 \leq 10 \text{ ms}$
- $0 \text{ ms} \leq T2 \leq 50 \text{ ms}$
- $200 \text{ ms} \leq T3$
- $10 \text{ ms} \leq T4$
- $10 \text{ ms} \leq T5$

- $0 \text{ ms} \leq T6$
- $10 \text{ ms} \leq T7$
- $200 \text{ ms} \leq T8$
- $0 \text{ ms} \leq T9 \leq 50 \text{ ms}$
- $1 \text{ s} \leq T10$

#### Notes:

1. When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

23 OF 35



京东方  
BOE**PRODUCT GROUP**

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

**10.0 Connector Description**

Physical interface is described as for the connector on LCM.

These connectors are capable of accommodating the following signals and will be following components.

**10.1 TFT LCD Module**

| Connector Name /Description | For Signal Connector              |
|-----------------------------|-----------------------------------|
| Manufacturer                | IPEX or Compatible                |
| Type/ Part Number           | I-PEX 20455-040E-12 or Compatible |
| Mating housing/ Part Number | I-PEX 20455-040T-11 or Compatible |

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

24 OF 35

京东方  
BOE**PRODUCT GROUP**

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

**11.0 MECHANICAL CHARACTERISTICS****11.1 Dimensional Requirements**

FIGURE 6 shows mechanical outlines for the model HT140WXB-601.  
Other parameters are shown in Table 9.

&lt;Table 9. Dimensional Parameters&gt;

| Parameter           | Specification                                 | Unit |
|---------------------|-----------------------------------------------|------|
| Active Area         | 309.40 (H) × 173.95 (V)                       |      |
| Number of pixels    | 1366 (H) X 768 (V) (1 pixel = R + G + B dots) |      |
| Pixel pitch         | 0.2265 (H) X 0.2265 (V)                       |      |
| Pixel arrangement   | RGB Vertical stripe                           |      |
| Display colors      | 262K                                          |      |
| Display mode        | Normally white                                |      |
| Dimensional outline | 323.5*192*5.2 (max)                           | mm   |
| Weight              | 350 (max)                                     | gram |
| Back Light          | Connector : MS24022P10                        |      |
|                     | LED, Horizontal-LED Array type                |      |

**10.2 Mounting**

See FIGURE 6.

**10.3 Glare and Polarizer Hardness.**

The surface of the LCD has an glare coating to maximize readability and hard coating to reduce scratching.

**10.4 Light Leakage**

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

25 OF 35



京东方  
BOE

## PRODUCT GROUP

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

## 12.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 10. Reliability test>

| No | Test Items                                       | Conditions                                                       |
|----|--------------------------------------------------|------------------------------------------------------------------|
| 1  | High temperature storage test                    | Ta = 60 °C, 240 hrs                                              |
| 2  | Low temperature storage test                     | Ta = -20 °C, 240 hrs                                             |
| 3  | High temperature & high humidity operation test  | Ta = 50 °C, 80%RH, 240 hrs                                       |
| 4  | High temperature operation test                  | Ta = 50 °C, 240 hrs                                              |
| 5  | Low temperature operation test                   | Ta = 0 °C, 240 hrs                                               |
| 6  | Thermal shock                                    | Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle                          |
| 7  | Vibration test<br>(non-operating)                | 1.5G, 10~500Hz, Half Sine<br>X,Y,Z / Sweep rate : 1 hour         |
| 8  | Shock test<br>(non-operating)                    | 220G, Half Sine Wave 2msec<br>±X, ±Y, ±Z Once for each direction |
| 9  | Electro-static discharge test<br>(non-operating) | Air : 150 pF, 330Ω, 15 KV<br>Contact : 150 pF, 330Ω, 8 KV        |

## 13.0 HANDLING & CAUTIONS

### (1) Cautions when taking out the module

- Pick the pouch only, when taking out module from a shipping package.

### (2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

### (3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

SPEC. NUMBER

—

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

26 OF 35



|                                                                                             |                 |     |            |
|---------------------------------------------------------------------------------------------|-----------------|-----|------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE |
|                                                                                             | TFT LCD PRODUCT | P1  | 2010.12.10 |

- (4) Cautions for the atmosphere
  - Dew drop atmosphere should be avoided.
  - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.
- (5) Cautions for the module characteristics
  - Do not apply fixed pattern data signal to the LCD module at product aging.
  - Applying fixed pattern for a long time may cause image sticking.
- (6) Other cautions
  - Do not disassemble and/or re-assemble LCD module.
  - Do not re-adjust variable resistor or switch etc.
  - When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

14.0 LABEL

(1) Product label

 **BOE**  
 **LCO**  
RoHS Compliant  
 **UL** <sup>®</sup> **US**

HT140WXB-601  
  
XXXXXXXXXXXXXXXXXXXX  
  
CN-OMNNJW-75261-  
XXX-XXXX-AXX  
MADE IN CHINA  
DP/N OMNNJW

| BUILD PHASE  |                                    | REVISION               |
|--------------|------------------------------------|------------------------|
| SST (WS)     |                                    | X00, X01, X02, ... X09 |
| PT (ES)      |                                    | X10, X11, X12, ... X19 |
| ST (CS)      |                                    | X20, X21, X23, ... X29 |
| XB (MP)      |                                    | A00, A01, A02, ... A99 |
| SPEC. NUMBER | SPEC TITLE                         | PAGE                   |
| -            | HT140WXB-601 Product Specification | 27 OF 35               |

|                                                                                                     |                      |     |            |
|-----------------------------------------------------------------------------------------------------|----------------------|-----|------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b> | REV | ISSUE DATE |
|                                                                                                     | TFT LCD PRODUCT      | P1  | 2010.12.10 |

### (2) High voltage caution label

|                                                                                   |                                                                              |                                                                                                                                                       |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | HIGH VOLTAGE<br>CAUTION                                                      | COLD CATHODE FLUORESCENT LAMP IN LCD<br>PANEL CONTAINS A SMALL AMOUNT<br>OF MERCURY. PLEASE FOLLOW LOCAL OR-<br>DINANCES OR REGULATIONS FOR DISPOSAL. |
|                                                                                   | RISK OF ELECTRIC SHOCK.<br>DISCONNECT THE ELECTRIC<br>POWER BEFORE SERVICING |                                                                                                                                                       |

### (3) Box label

Label Size: 110 mm (L) × 56 mm (W)

Contents


Model: HT140WXB-601

Q`ty: Module Q`ty in one box

Serial No.: Box Serial No. See next figure for detail description.

Date: Packing Date

Internal use of Product



|      |       |      |      |       |              |           |
|------|-------|------|------|-------|--------------|-----------|
| 00   | 0     | 0    | 00   | 0     | 0000         | 000000    |
| Type | Grade | Line | Year | Month | Internal use | Serial No |

|                   |                                                  |                  |
|-------------------|--------------------------------------------------|------------------|
| SPEC. NUMBER<br>- | SPEC TITLE<br>HT140WXB-601 Product Specification | PAGE<br>28 OF 35 |
|-------------------|--------------------------------------------------|------------------|

京东方  
BOE**PRODUCT GROUP**

TFT LCD PRODUCT

REV

P1

ISSUE DATE


2010.12.10

**15.0 PACKING INFORMATION****15.1 Packing order**



Put Pad into the box.



As shown in the figure, place the paper spacer and modules bundled by PE bag in the box.



After sealing the box, attach Packing Label on the attach position sign area of the box.



Place Cover Pad on the top of the box.

**15.2 Notes**

- Box Dimension: 526mm(W) x 346mm(D) x 448mm(H)
- Package Quantity in one Box: 38pcs
- Total Weight: 16kg

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

29 OF 35



**京东方  
BOE****PRODUCT GROUP**

TFT LCD PRODUCT

REV


P1

ISSUE DATE

2010.12.10

**16.0 MECHANICAL OUTLINE DIMENSION**

Figure 6. TFT-LCD Module Outline Dimension (Front View)



SPEC. NUMBER

-

SPEC TITLE


HT140WXB-601 Product Specification

PAGE

30 OF 35

2010.12.10

Figure 7. TFT-LCD Module Outline Dimensions (Rear view)

31 OF 35





|  京东方<br>BOE |     | PRODUCT GROUP                      |     |               | REV                                 | ISSUE DATE |
|---------------------------------------------------------------------------------------------|-----|------------------------------------|-----|---------------|-------------------------------------|------------|
|                                                                                             |     | TFT LCD PRODUCT                    |     |               | P1                                  | 2010.12.10 |
| Address<br>(HEX)                                                                            | Hex | Dec                                | crc | Input values. | Notes                               |            |
| 00                                                                                          | 00  | 0                                  |     | 0             | EDID Header                         |            |
| 01                                                                                          | FF  | 255                                |     | 255           |                                     |            |
| 02                                                                                          | FF  | 255                                |     | 255           |                                     |            |
| 03                                                                                          | FF  | 255                                |     | 255           |                                     |            |
| 04                                                                                          | FF  | 255                                |     | 255           |                                     |            |
| 05                                                                                          | FF  | 255                                |     | 255           |                                     |            |
| 06                                                                                          | FF  | 255                                |     | 255           |                                     |            |
| 07                                                                                          | 00  | 0                                  |     | 0             | ID = BOE                            |            |
| 08                                                                                          | 09  | 9                                  |     | BOE           |                                     |            |
| 09                                                                                          | E5  | 229                                |     | 1440          | ID = 1440                           |            |
| 0A                                                                                          | A0  | 160                                |     |               |                                     |            |
| 0B                                                                                          | 05  | 5                                  |     |               |                                     |            |
| 0C                                                                                          | 00  | 0                                  |     |               |                                     |            |
| 0D                                                                                          | 00  | 0                                  |     |               |                                     |            |
| 0E                                                                                          | 00  | 0                                  |     |               |                                     |            |
| 0F                                                                                          | 00  | 0                                  |     |               |                                     |            |
| 10                                                                                          | 1   | 1                                  |     | 1             |                                     |            |
| 11                                                                                          | 14  | 20                                 |     | 2010          | Manufactured in 2010                |            |
| 12                                                                                          | 01  | 1                                  |     | 1             | EDID Ver 1.0                        |            |
| 13                                                                                          | 04  | 4                                  |     | 4             | EDID Rev. 0.4                       |            |
| 14                                                                                          | 80  | 128                                |     | -             |                                     |            |
| 15                                                                                          | 1F  | 31                                 |     | 31            | 31 cm (Approx)                      |            |
| 16                                                                                          | 11  | 17                                 |     | 17            | 17 cm (Approx)                      |            |
| 17                                                                                          | 78  | 120                                |     | 2.2           | Gamma curve = 2.2                   |            |
| 18                                                                                          | 0A  | 10                                 |     |               | RGB display, Preferred Timming mode |            |
| 19                                                                                          | D2  | 210                                |     | -             | Red / Green Low Bits                |            |
| 1A                                                                                          | 40  | 64                                 |     | -             | Blue / White Low Bits               |            |
| 1B                                                                                          | 95  | 149                                | 595 | 0.582         | Red (x) = 10010101 (0.582)          |            |
| 1C                                                                                          | 5A  | 90                                 | 361 | 0.353         | Red (y) = 01011010 (0.353)          |            |
| 1D                                                                                          | 53  | 83                                 | 332 | 0.325         | Green (x) = 01010011 (0.325)        |            |
| 1E                                                                                          | 8C  | 140                                | 562 | 0.549         | Green (y) = 10001100 (0.549)        |            |
| 1F                                                                                          | 26  | 38                                 | 153 | 0.150         | Blue (x) = 00100110 (0.15)          |            |
| 20                                                                                          | 1C  | 28                                 | 112 | 0.110         | Blue (y) = 00011100 (0.11)          |            |
| 21                                                                                          | 50  | 80                                 | 320 | 0.313         | White (x) = 01010000 (0.313)        |            |
| 22                                                                                          | 54  | 84                                 | 336 | 0.329         | White (y) = 01010100 (0.329)        |            |
| SPEC. NUMBER                                                                                |     | SPEC TITLE                         |     |               |                                     | PAGE       |
| -                                                                                           |     | HT140WXB-601 Product Specification |     |               |                                     | 32 OF 35   |



|  <b>京东方<br/>BOE</b> |     | <b>PRODUCT GROUP</b>               |     |               | REV                                                 | ISSUE DATE |
|-----------------------------------------------------------------------------------------------------|-----|------------------------------------|-----|---------------|-----------------------------------------------------|------------|
|                                                                                                     |     | TFT LCD PRODUCT                    |     |               | P1                                                  | 2010.12.10 |
| Address<br>(HEX)                                                                                    | Hex | Dec                                | crc | Input values. | Notes                                               |            |
| 23                                                                                                  | 00  | 0                                  |     | -             |                                                     |            |
| 24                                                                                                  | 00  | 0                                  |     | -             |                                                     |            |
| 25                                                                                                  | 00  | 0                                  |     | -             |                                                     |            |
| 26                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 27                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 28                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 29                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 2A                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 2B                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 2C                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 2D                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 2E                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 2F                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 30                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 31                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 32                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 33                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 34                                                                                                  | 01  | 1                                  |     |               | Not Used                                            |            |
| 35                                                                                                  | 01  | 1                                  |     |               |                                                     |            |
| 36                                                                                                  | E4  | 228                                |     | 71.4          | 71.4MHz Main clock                                  |            |
| 37                                                                                                  | 1B  | 27                                 |     |               |                                                     |            |
| 38                                                                                                  | 56  | 86                                 |     | 1366          | Hor Active = 1366                                   |            |
| 39                                                                                                  | 7A  | 122                                |     | 122           | Hor Blanking = 122                                  |            |
| 3A                                                                                                  | 50  | 80                                 |     | -             | 4 bits of Hor. Active + 4 bits of Hor. Blanking     |            |
| 3B                                                                                                  | 00  | 0                                  |     | 768           | Ver Active = 768                                    |            |
| 3C                                                                                                  | 20  | 32                                 |     | 32            | Ver Blanking = 32                                   |            |
| 3D                                                                                                  | 30  | 48                                 |     | -             | 4 bits of Ver. Active + 4 bits of Ver. Blanking     |            |
| 3E                                                                                                  | 30  | 48                                 |     | 48            | Hor Sync Offset = 48                                |            |
| 3F                                                                                                  | 20  | 32                                 |     | 32            | H Sync Pulse Width = 32                             |            |
| 40                                                                                                  | 36  | 54                                 |     | 3             | V sync Offset = 3 line                              |            |
| 41                                                                                                  | 00  | 0                                  |     | 6             | V Sync Pulse width : 6 line                         |            |
| 42                                                                                                  | 35  | 53                                 |     | 309           | Horizontal Image Size = 309 mm (Low 8 bits)         |            |
| 43                                                                                                  | AD  | 173                                |     | 173           | Vertical Image Size = 173 mm (Low 8 bits)           |            |
| 44                                                                                                  | 10  | 16                                 |     | -             | 4 bits of Hor Image Size + 4 bits of Ver Image Size |            |
| 45                                                                                                  | 00  | 0                                  |     | 0             | Hor Border (pixels)                                 |            |
| 46                                                                                                  | 00  | 0                                  |     | 0             | Vertical Border (Lines)                             |            |
| 47                                                                                                  | 1A  | 26                                 |     |               | Refer to right table                                |            |
| SPEC. NUMBER                                                                                        |     | SPEC TITLE                         |     |               |                                                     | PAGE       |
| -                                                                                                   |     | HT140WXB-601 Product Specification |     |               |                                                     | 33 OF 35   |



|  京东方<br>BOE |     | <b>PRODUCT GROUP</b>                             |     |               | REV                                                 | ISSUE DATE       |
|---------------------------------------------------------------------------------------------|-----|--------------------------------------------------|-----|---------------|-----------------------------------------------------|------------------|
|                                                                                             |     | TFT LCD PRODUCT                                  |     |               | P1                                                  | 2010.12.10       |
| Address<br>(HEX)                                                                            | Hex | Dec                                              | crc | Input values. | Notes                                               |                  |
| 48                                                                                          | 30  | 48                                               |     | 56.8          | 56.8MHz Main clock                                  |                  |
| 49                                                                                          | 16  | 22                                               |     |               |                                                     |                  |
| 4A                                                                                          | 56  | 86                                               |     | 1366          | Hor Active = 1366                                   |                  |
| 4B                                                                                          | 00  | 0                                                |     | 256           | Hor Blanking = 256                                  |                  |
| 4C                                                                                          | 51  | 81                                               |     | -             | 4 bits of Hor. Active + 4 bits of Hor. Blanking     |                  |
| 4D                                                                                          | 00  | 0                                                |     | 768           | Ver Active = 768                                    |                  |
| 4E                                                                                          | 6C  | 108                                              |     | 108           | Ver Blanking = 108                                  |                  |
| 4F                                                                                          | 30  | 48                                               |     | -             | 4 bits of Ver. Active + 4 bits of Ver. Blanking     |                  |
| 50                                                                                          | 30  | 48                                               |     | 48            | Hor Sync Offset = 48                                |                  |
| 51                                                                                          | 20  | 32                                               |     | 32            | H Sync Pulse Width = 32                             |                  |
| 52                                                                                          | 36  | 54                                               |     | 3             | V sync Offset = 3 line                              |                  |
| 53                                                                                          | 00  | 0                                                |     | 6             | V Sync Pulse width : 6 line                         |                  |
| 54                                                                                          | 35  | 53                                               |     | 309           | Horizontal Image Size = 309 mm (Low 8 bits)         |                  |
| 55                                                                                          | AD  | 173                                              |     | 173           | Vertical Image Size = 173 mm (Low 8 bits)           |                  |
| 56                                                                                          | 10  | 16                                               |     | -             | 4 bits of Hor Image Size + 4 bits of Ver Image Size |                  |
| 57                                                                                          | 00  | 0                                                |     | 0             | Hor Border (pixels)                                 |                  |
| 58                                                                                          | 00  | 0                                                |     | 0             | Vertical Border (Lines)                             |                  |
| 59                                                                                          | 1A  | 26                                               |     |               | ASCII Data Sting Tag                                |                  |
| 5A                                                                                          | 00  | 0                                                |     |               |                                                     |                  |
| 5B                                                                                          | 00  | 0                                                |     |               |                                                     |                  |
| 5C                                                                                          | 00  | 0                                                |     |               |                                                     |                  |
| 5D                                                                                          | FE  | 254                                              |     |               |                                                     |                  |
| 5E                                                                                          | 00  | 0                                                |     |               | D/PN: MNNJW                                         |                  |
| 5F                                                                                          | 4D  | 77                                               |     | M             |                                                     |                  |
| 60                                                                                          | 4E  | 78                                               |     | N             |                                                     |                  |
| 61                                                                                          | 4E  | 78                                               |     | N             |                                                     |                  |
| 62                                                                                          | 4A  | 74                                               |     | J             |                                                     |                  |
| 63                                                                                          | 57  | 87                                               |     | W             | EDID: A00                                           |                  |
| 64                                                                                          | 80  | 128                                              |     | 10000000      | BOE PN                                              |                  |
| 65                                                                                          | 48  | 72                                               |     | H             |                                                     |                  |
| 66                                                                                          | 54  | 84                                               |     | T             |                                                     |                  |
| 67                                                                                          | 31  | 49                                               |     | 1             |                                                     |                  |
| 68                                                                                          | 34  | 52                                               |     | 4             |                                                     |                  |
| 69                                                                                          | 36  | 54                                               |     | 6             |                                                     |                  |
| 6A                                                                                          | 30  | 48                                               |     | 0             |                                                     |                  |
| 6B                                                                                          | 31  | 49                                               |     | 1             |                                                     |                  |
| SPEC. NUMBER<br>-                                                                           |     | SPEC TITLE<br>HT140WXB-601 Product Specification |     |               |                                                     | PAGE<br>34 OF 35 |





京东方  
BOE

## PRODUCT GROUP

TFT LCD PRODUCT

REV

P1

ISSUE DATE

2010.12.10

| Address (HEX) | Hex | Dec | crc | Input values. | Notes                                        |
|---------------|-----|-----|-----|---------------|----------------------------------------------|
| 68            | 34  | 52  |     | 4             | BOE PN                                       |
| 69            | 36  | 54  |     | 6             |                                              |
| 6A            | 30  | 48  |     | 0             |                                              |
| 6B            | 31  | 49  |     | 1             |                                              |
| 6C            | 00  | 0   |     |               | Product Name Tag (ASCII)                     |
| 6D            | 00  | 0   |     |               |                                              |
| 6E            | 00  | 0   |     |               |                                              |
| 6F            | 00  | 0   |     |               |                                              |
| 70            | 00  | 0   |     |               |                                              |
| 71            | 00  | 0   |     | 00000000      | 6-bit Color Depth & no FRC                   |
| 72            | 41  | 65  |     | 01000001      | WLED & singal light bar & one light bar      |
| 73            | 01  | 1   |     | 00000001      | Frame rate 40Hz~65Hz                         |
| 74            | 94  | 148 |     | 10010100      | Light Controller:PWM & Max. Luminance 200    |
| 75            | 00  | 0   |     | 00000000      | Front Surface:Anti-Glare & RGB v-stripe      |
| 76            | 00  | 0   |     | 00000000      | no NTSC & no DBC                             |
| 77            | 00  | 0   |     | 00000000      | no Motion Blur & no Active Gamma             |
| 78            | 00  | 0   |     | 00000000      | no Wireless Enhancement & no In-Cell Scanner |
| 79            | 01  | 1   |     | 00000001      | Single LVDS                                  |
| 7A            | 01  | 1   |     | 00000001      | Built-In Self Test                           |
| 7B            | 0A  | 10  |     |               |                                              |
| 7C            | 20  | 32  |     |               |                                              |
| 7D            | 20  | 32  |     |               |                                              |
| 7E            | 00  | 0   |     |               |                                              |
| 7F            | 73  | 115 | 115 | -             |                                              |

SPEC. NUMBER

-

SPEC TITLE

HT140WXB-601 Product Specification

PAGE

35 OF 35